

## ELITE WORK POSITIONING LANYARD WITH GRIP ADJUSTER

AFL405111

KStrong has developed a range of Work Positioning Lanyards/ Pole Strap to be used in conjunction with a fall arrest Harness or Work Positioning Belt to provide additional support to the user, allowing them to work more comfortable and safer.

**Note:** A Work Positioning Lanyard/ Pole Strap must be used in conjunction with a fall arrest Harness and a separate fall arrest device such as a fall arrest Lanyard or an inertia reel.

### FEATURES

- Twisted Rope 14mm
- Twist Lock Karabiner
- Rope Grab Steel
- Abrasion Resistant Thimbles
- Compass Asset Technology

### HOW TO USE

Refer to User Instruction Manual



SCAN TO DOWNLOAD

### MATERIAL COMPONENTS

Metal Components: Rope grab (AFG801005) Steel, MBS 15kN  
Karabiners (AFC601100) Steel, MBS 25kN  
Stitching Thread: High Tenacity Polyester (Colour Contrasted)  
Twisted Rope: 14mm 3 Strand Polyamide Twisted Rope, MBS 25kN

### WEIGHT

1.07kg

### LENGTH

2.0m

### CAPACITY

140kg

### RELEVANT STANDARDS

EN 358:2018

